

# DATALOCKER SENTRY 5 HARDWARE ENCRYPTED USB



TAA-compliant, NATO-trusted Encrypted USB with Mandatory Password Protection

## UNCOMPROMISED SECURITY. ULTIMATE COMPLIANCE.



FIPS 140-3 Level 3 (pending)\*  
hardware-based AES 256-bit  
XTS mode encryption



MIL-STD-810F and IP68  
certified, extremely rugged  
solid zinc metal casing  
encapsulated in FIPS 140-3  
tamper-resistant epoxy



Zero-Touch Deployment to  
SafeConsole® Predeployment,  
available via Professional  
Services, streamlines rollout  
and saves additional time and  
cost for organizations



Sentry 5 is tailored for organizations that prioritize data protection and compliance. It features robust security measures, including password protection and AES 256-bit XTS mode encryption, ensuring top-tier security for sensitive data. This device is exclusively managed through SafeConsole, (sold separately), which enhances its capabilities.

SafeConsole automates inventory management, policy enforcement, and audit processes, making Sentry 5's administration efficient and streamlined. In terms of physical durability, Sentry 5 is designed to withstand harsh conditions, being rugged, waterproof, and tamper-resistant.

Furthermore, its compatibility with various operating systems adds to its versatility, making it a suitable choice for diverse IT environments. The combination of stringent security, mandatory SafeConsole management, durable design, and broad compatibility positions Sentry 5 as a comprehensive security solution for organizations with stringent security and regulatory requirements.

## SECURE USB FLASH DRIVE FOR COMPLIANCE

- FIPS 140-3 Level 3 (pending)\*
- Password protected with hardware-based AES 256-bit XTS mode encryption
- Meets CMMC, HIPAA, SOX, SOC2, ISO 27001, NIS2, CCPA, and GDPR requirements
- Assembled in the USA
- TAA-compliant, NATO-trusted supply chain
- 5-year device warranty out of the box
- Streamlined for large organizations with DataLocker SafeConsole device management, automated inventory, policies, audit, integrates (API, SIEM, SSO), available as On-Prem & SaaS
- Requires a mandatory password in included portable device software, verified in hardware, before accessing hardware encrypted files
- Read-Only Mode to combat ransomware
- Zero-Touch Deployment available with DataLocker Professional Services (sold separately)
- Gain immediate access to the most current DataLocker device software releases, ensuring a comprehensive and up-to-date solution
- Compatible with Windows® and macOS®. Limited capability on Linux



Get a Custom Demo

[datalocker.com](https://datalocker.com) | [sales@datalocker.com](mailto:sales@datalocker.com)

## SECURE USB FLASH DRIVE FOR COMPLIANCE

- Digitally signed firmware, making it immune to BadUSB
- Ruggedized and Waterproof. Solid zinc metal casing sealed with tamper-resistant epoxy
- IP68 certified: up to 6.5 feet of water (2.0 meters)
- MIL-STD-810F certified: crash, drop, shock, vibration, and immersion
- Internal and external serial number matching
- Available as forced managed with a SafeConsole® license (sold separately).
- USB 3.2 Gen 1 (type A), USB-C accessory available for purchase (SKU# CBLUSBAFCM)
- Eco-friendly paper packaging

### MANAGED BY SAFECONSOLE FEATURES

- Automated device/user inventory
- Remote password reset and actions
- Device and file audit for compliance
- Custom device policies for password and usage
- Portable Trellix™ Enterprise Anti-malware

**USB Security Experts**—DataLocker Inc. knows encrypted USB like no one else. Our team created and patented the first secure pin pad drive in 2007, the SafeConsole central management server in 2009, followed by PortBlocker USB control in 2018. We help protect data on millions of devices for government and enterprises that require stringent compliance.

FIPS 140-3 LEVEL 3  
(PENDING)\*

TAA-COMPLIANT

IP68 & MIL-STD-810F

CRYPTOGRAPHIC ERASURE  
NIST 800:80  
CLEAN MEDIA

ZERO-TOUCH  
DEPLOYMENT

## TECHNICAL SPECIFICATIONS

### CAPACITIES

8GB, 16GB, 32GB, 64GB,  
128GB, 256GB, 512GB

### DIMENSIONS

L: 3.13 inches (79.5 mm)  
W: 0.79 inch (20 mm)  
D: 0.39 inch (10 mm)

### WEIGHT

1.76 oz (50 grams)

### CRYPTOGRAPHIC PROCESS

FIPS 140-3 Level 3 Device  
Certified (pending)\*  
Password protected with  
hardware-based AES 256-bit  
XTS mode encryption

### TEMPERATURE

Operating: 0°C to 50°C  
Storage: -20°C to 85°C

### STANDARDS AND CERTIFICATION

FIPS 140-3 Level 3 (pending)\*  
TAA-compliant  
UKCA  
FCC  
CE  
KC  
Wee  
Canada ICES  
RCM (Australia/NZ)  
Taiwan BSMI, RoHS  
Japan VCCI  
China RoHS  
IP68 & MIL-STD-810F  
NIST 800:88

### INTERFACE

USB 3.2 Gen 1 (type A),  
USB-C accessory available  
for purchase (SKU#  
CBLUSBAFCM)

### TRANSFER SPEEDS

8GB - 128GB: 260MB/s read,  
190MB/s write  
256GB: 240MB/s read,  
170MB/s write  
512GB: 310MB/s read,  
250MB/s write

### USB 2.0

8GB - 512GB: 30MB/s read,  
20MB/s write

### DEVICE LANGUAGES

English, French, Spanish,  
German, Japanese, Korean,  
Traditional Chinese, and  
Simplified Chinese

### SYSTEM COMPATIBILITY

Compatible with Windows®  
and macOS®. Limited  
compatibility on Linux  
USB 3.0/USB 3.1/USB 3.2  
Gen 1 compliant and 2.0  
compatible

### RUGGEDIZED, DUST & WATERPROOF

IP68 (up to 6.5 feet of water,  
2.0 meters), MIL-STD-810F  
certified: crash, drop, shock,  
vibration, immersion.  
Product must be clean and  
dry before use.

Solid zinc metal casing  
sealed with tamper-resistant  
epoxy.

### PART NUMBERS

S5-008-FE-M  
S5-016-FE-M  
S5-032-FE-M  
S5-064-FE-M  
S5-128-FE-M  
S5-256-FE-M  
S5-512-FE-M

Available as forced managed  
(-M) with a SafeConsole®  
license (sold separately).

### WARRANTY

5-year device warranty out  
of the box

\*The Sentry5 has been designed for FIPS 140-3 Level 3 and is being tested by an accredited NIST lab. The product is in process for certification and is officially listed by NIST.



Get a Custom Demo

[datalocker.com](https://datalocker.com) | [sales@datalocker.com](mailto:sales@datalocker.com)