



DATALOCKER SENTRY ONE ENCRYPTED FLASH DRIVE



FIPS 140-2 level 3 Validated Flash Drive

SECURE. MOBILE. FAST.



FIPS 140-2 Level 3 Certified
Hardware-based AES 256-bit XTS mode encryption



Tamper evident seal and waterproof up to ~5 ft
Conforms to IEC 60529 IPX8
IP68 Certified



Remotely manageable with SafeConsole

DataLocker Sentry ONE offers advanced security with FIPS 140-2 Level 3 certification and a tamper evident seal for physical security. The entire drive is FIPS certified, not just the controller, and its AES 256-bit hardware-based encryption in XTS mode offers unsurpassed security.

Powerful Encryption Right Out Of The Box

Everything you need to encrypt data is built into the FIPS 140-2 Level 3 certification. No drivers. No setup. Just iron-clad, hardware-based AES 256-bit encryption in an easy-to-use interface, which is further guarded by an army of automated security policies.

Protect Data at Scale

Remote management available with SafeConsole®, lets admins fully control or terminate devices over the Internet. Rapid, no-hands, automated deployment at scale is available for managed Sentry ONE drives.

Remotely Manage & Audit Your Entire Fleet

Sentry ONE drives are remotely manageable with SafeConsole, giving admins the ability to remotely lock or wipe drives, reset passwords, view last-used locations, and see what data has been added, removed, or changed on the drive. Set device or group-specific policies for all the drives in your fleet.



Get a Custom Demo

datalocker.com | sales@datalocker.com

THE SENTRY ONE ENCRYPTED FLASH DRIVE

FIPS 140-2 LEVEL 3 CERTIFICATION

FIPS 140-2 level 3 certification. Provides always-on hardware based encryption. Dedicated AES 256-bit XTS mode crypto engine meets rigorous cryptographic standards and is more secure than software-based alternatives. Hardened internals and enclosure for increased physical security.

ADMIN POLICIES & USER DATA RECOVERY

Admins can set rigorous password policies (non-sequential, non-repeating special characters, minimum characters). Should users forget a password, admins can generate a Recovery Code that allows the user to access their device and change their password without losing any data.

FULLY MANAGEABLE DEVICE

Use DataLocker SafeConsole to manage individual and groups of devices using automated policies.

READ-ONLY MODE

Admins can configure the Sentry ONE to read-only mode, ensuring that no malicious data can be written to the device.

BRUTE FORCE PASSWORD PROTECTION

Admins can configure how many failed password attempts are needed before the device destroys its payload.

THE SENTRY ONE MANAGED FEATURES (Requires SafeConsole)

REMOTE DEVICE DETONATION

Lets admins functionally destroy the device and its data remotely to protect against data or encryption key theft.

ON BOARD ANTI-MALWARE

Automatically scans files and quarantines/destroys bad apps/files based on policy settings.

DATA GEOFENCING

SafeConsole uses geofencing, trusted networks, and ZoneBuilder to ensure a device changes its security posture based on its location.

COMPREHENSIVE AUDIT CAPABILITIES

Have a complete record of file activity (including name changes on the device), password attempts, device locations and machines, device health, and policies in force.

TECHNICAL SPECIFICATIONS

CAPACITIES

8GB, 16GB, 32GB
64GB, 128GB

DIMENSIONS

L: 7.79 cm (3.07 in)
W: 2.22 cm (.87 in)
D: 1.21 cm (.47 in)

WEIGHT

54 grams / 1.9 oz

CRYPTOGRAPHIC PROCESS

FIPS 140-2 Level 3 Device Certified ([Cert. #2929](#)).
AES 256-bit hardware XTS mode

TEMPERATURE

Operating: 0°C to 60°C
CStorage: -20°C to 85°C

STANDARDS AND CERTIFICATION

FIPS 140-2 Level 3 ([Cert. #2929](#))
IP68 Certified
CSPN-2022/07⁴
TAA Compliance
FCC
CE
VCCI & KC
RoHS & WEEE

INTERFACE

USB 3.2 Gen 1 - Backward compatible with USB 2.0 & 1.1

TRANSFER SPEEDS

USB 3.2 GEN 1:
8GB & 16GB: 165MB/s READ,
22MB/s WRITE
32GB: 250MB/s read,
40MB/s WRITE
64GB & 128GB: 250MB/s
READ, 85MB/s WRITE
USB 2.0:
8GB-128GB: 30MB/s READ,
20MB/S WRITE

WATERPROOF

Up to -5ft; Conforms to IEC 60529 IPX8. IP68 Certified..
Product must be clean and dry before use.

SYSTEM COMPATIBILITY

Compatible with Windows® and macOS®. Limited compatibility on Linux
Citrix Ready (XenDesktop, XenApp compatible)

Sentry ONE current Unified Client version (6.6.0) is compatible with both the M1 and M2 processors.

Two (2) free drive letters required for use on Windows

PART NUMBERS

SONE008
SONE016
SONE032
SONE064
SONE128
SONE008M
SONE016M
SONE032M
SONE064M
SONE128M

WARRANTY

5-year limited warranty

1 Some of the listed capacity on a Flash storage device is used for formatting and other functions and thus is not available for data storage. As such, the actual available capacity for data storage is less than what is listed on the products.

2 Online management features not available for Linux.

3 Speed may vary due to host hardware, software and usage.

4 This CSPN certificate is recognised by the Federal Office for Information Security (BSI) as comparable to a certificate according to the Beschleunigte Sicherheitszertifizierung (BSZ) scheme.



Get a Custom Demo

datalocker.com | sales@datalocker.com